



Microcom Design, Inc.

Wind Monitor Model 05103

P/N: W-103



The **Wind Monitor**, wind speed/wind direction sensor is both simple and lightweight. Corrosion resistant construction, and the elimination of slip rings and brushes combine to make a reliable wind sensor. The wind speed sensor is a helicoid shape propeller molded of polypropylene plastic. The four-blade propeller is 18 cm diameter x 30 cm pitch with a distance constant of 2.7 meters or 8.8 feet. Threshold of the propeller is 1 m/sec. Propeller rotation produces an AC sine wave voltage signal with frequency directly proportional to wind speed. The AC voltage signal is induced in a centrally mounted coil located on the non-rotating portion of the main mounting assembly, eliminating the need for slip rings and brushes. The vane assembly has a threshold below 1.3 m/s with a damping ratio of 0.25. Vane position is transmitted through a coupling to a precision conductive plastic potentiometer located in sealed chamber in the center of the main housing. The potentiometer requires a regulated excitation voltage, which outputs an analog voltage directly proportional to azimuth angle. All transducer leads terminate in a junction box on the mounting post, making sensor cable connections easy and convenient. Four conductors are required. The tail assembly is thermo-formed of rigid U.V. stabilized plastic, and the main housing assembly and other internal parts are injection-molded. Propeller shaft bearings and vertical shaft bearings are sealed stainless steel precision-grade ball bearings, which further contribute to the sensors' ruggedness.

Specifications

Range

Wind Speed: 134 mph (0-60 m/sec)
Gust Survival: 220 mph (100 m/sec)
Azimuth: 360° mechanical (355° electrical 5° open)

Threshold

Propeller Sensitivity: 2.2 mph (1.0 m/sec)
Vane Sensitivity: 0.9 m/sec at 10°, 0.7 m/sec at 5°

Propeller Distance Constant: 6.9 feet (2.1m) for 63% recovery

Vane Delay Distance: 3.9 feet (1.2m) for 50% recovery

Damping Ratio: 0.45

Accuracy

Wind Speed: ± 0.6 mph (± 0.3 m/sec)
Wind Direction: ± 3°

Dimensions

Height: 15.0 in (38 cm)
Length: 15.0 in (38 cm)
Propeller Diameter: 7.9 in (20 cm)
Mounting: 1.34 in (34 mm) dia

Sensor Weight: 1.5 lbs (0.7 kg)



Microcom Design, Inc.

10948 Beaver Dam Road
Hunt Valley, MD, USA 21030
Tel: (410) 771-1070
Fax: (410) 771-0018

E-mail: sales@microcomdesign.com

Microcom Design Inc.

656-E Capital Circle, NE
Tallahassee, FL, USA 32301
Tel: (850) 325-1865

Email: sales@microcomdesign.com

Microcom Canada

Omnimatrix
3465 Ashby
Saint Laurent, QC H4R 2K3
Tel: (514) 684 1004
Fax: (514) 697 0400

Email: roger@omnimatrix.com

Microcom Brazil

Simtech Representacoes LTDA
Rua do Mercado 17/14 andar Centro
Rio de Janeiro, Brazil CEP 20010-120
Tel: 21 2506 5900
Fax: 21 2240 1242

E-mail: simtech@simtech.com.br